KOBIT
s.r.o.
stroje pro údržbu a opravy silnic

INERT AND CHEMICAL MATERIAL SPREADER **SYKO 2, 2,5, 3**




Body capacity	2 - 3 m³
Material excavation	worm / belt
Drive	hydraulics, auxiliary engine
Dosing - salt/inert	5 - 50 g/m² / 50 - 300 g/m²
Basic brine/salt ratio	1 : 3
Control	semiautomatic or automatic

Spreading width	2 - 8 m
Operating speed	3 - 60 km/h
Supply voltage	12 - 24 V
Speed reading	from tacho output
Superstructure weight	650 - 750 kg
Electronic control, test button	included

INERT AND CHEMICAL MATERIAL SPREADER **SYKO 4, 5, 6**




Body capacity	4 - 6 m³
Material excavation	1x worm / 2x worm / belt
Drive	hydraulics, auxiliary engine
Dosing - salt/inert	5 - 40 g/m² / 50 - 300 g/m²
Basic brine/salt ratio	1 : 3
Control	semiautomatic or automatic

Spreading width	2 - 8 m
Operating speed	3 - 60 km/h
Supply voltage	12 - 24 V
Speed reading	from tacho output
Superstructure weight	1 430 - 1750 kg
Electronic control, test button	included

INERT AND CHEMICAL MATERIAL SPREADER **SYKO 7, 8**




Body capacity	7,2 - 8,2 m³
Material excavation	1x worm / 2x worm / belt
Drive	hydraulics, auxiliary engine
Dosing - salt/inert	5 - 50 g/m² / 50 - 300 g/m²
Basic brine/salt ratio	1 : 3
Control	semiautomatic or automatic

Spreading width	2 - 12 m
Operating speed	5 - 60/70 km/h
Supply voltage	12 - 24 V
Speed reading	from tacho output
Superstructure weight	1 890 - 2 050 kg / 1 960 - 2 070 kg
Electronic control, test button	included